



## Optical Splitter Shelf

The LightLink LanSystem™ Optical Splitter Shelf provides a convenient in-rack solution to combine/split optical signals in a passive optical network. With 1x16, 1x32 and 2x32 options available, the splitter shelf also features a Planar Lightwave Circuit (PLC) allowing a signal to be split into either 16 or 32 channels in a 1U rack-mountable housing. The 2x32 option provides a filter WDM concatenated to a PLC, which allows 1310/1490/1550 nm signal management evenly across 32 channels.

### Features

- Telcordia® GR-63 NEBS tested housing
- Aluminum Material per ASTM B209
- Universal Mounting Bracket WECO, EIA
- 19" and 23" Rack Mountable
- Rugged construction, ensuring environmental, mechanical and optical integrity
- WDM and PLC fully compliant to Telcordia GR-1209 and GR-1221
- Low Excess loss
- Low Polarization Dependent Loss

### Applications

- PON-FTTx Networks
- CATV links
- DWDM and CWDM systems
- Wide area networks
- Outside plant requirements

### Specifications

PARAMETER	1x16	1x32	2x32	
Insertion Loss	13.5 ~ 14.3 dB	17.5 - 18.5 dB	17.5 - 19 dB	
Uniformity	1.5 dB Typical	1.8 dB Typical	1.8 dB Typical	
PDL	≤ 0.3 dB	<0.45 dB	<0.45 dB	
Return Loss	≥ 55 dB	≥ 55 dB	≥ 40 dB	
Directivity	≥ 55 dB	≥ 55 dB	≥ 50 dB	
Fiber Type	SMF-28e	SMF-28e	SMF-28e	
Operating Temp	-40°C to +85°C	-40°C to +85°C	-40°C to +70°C	
Storage Temp	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	
Operating Bandwidth	1260 ~ 1650	1260 ~ 1650	1550 nm Band - Port 1 (Pass)	1550 - 1560 nm
			1310 + 1490 nm - Port 2 (Reflect)	1260-1360 nm & 1480-1500 nm

### Ordering Information

DESCRIPTION	AFL NO.
1x16 Optical Splitter Shelf, ASC inputs/outputs, 1U, textured White	FM001000
1x32 Optical Splitter Shelf, ASC inputs/outputs, 1U, textured White	FM000775
2x32 Optical Splitter Shelf, ASC inputs/outputs, 1U, textured White	FM000622

### Qualifications

GOVERNING BODY	STANDARD CODE
ASTM	ASTM B209
Telcordia	GR-63NEBS, GR-1209 and GR-1221