



FUSEConnect MPO Connectors, Cable



FUSEConnect MPO Connectors, Ribbon

## FUSEConnect® MPO Splice-On, Field-Installable Connectors with Heat Sleeve

AFL's FUSEConnect MPO splice-on, field-installable connectors are uniquely designed and feature just six components. The innovative factory pre-polished ferrule allows for a field-termination process that eliminates the need for polishing, adhesives and crimping in the field and minimizes the potential for operator error and expensive connector scrap. FUSEConnect MPO is part of the FUSEConnect splice-on connector family which includes SC, LC, ST and FC style connectors.

This updated design for the FUSEConnect MPO replaces the mechanical clamp splice protector with a heat protection sleeve utilizing the on-board splicer heater eliminating the need for a separate mechanical clamp tool. The connector is designed for use with the new RT-02 ribbonizing tool which does not require ribbonizing glue resulting in a cleaner termination process.

FUSEConnect MPO performs as an equivalent to the standard factory terminated MPO/MTP® assemblies. Designed to utilize standard ribbon, SpiderWeb Ribbon®, or loose tube cable, this connector helps minimize the complexity involved in the termination of a multi-fiber connection, allowing for a reliable and repeatable termination in field applications. AFL offers a tool kit as well as a variety of accessories designed to meet all your installation needs for your FUSEConnect MPO application.

### Features

- Field installable splice-on connector
- Heat sleeve style splice protector
- Utilizes RT-02 ribbonizing tool for glueless termination process
- Only six components
- No adhesives, crimping or polishing
- Field MPO polarity customization
- Includes 3.0 mm round and flat ribbon boots in each pack

### Applications

- Connectorization in:
  - RF-overlay FTTP networks
  - Cable TV backbone networks
  - Outside plant
  - MDU FTTP Cabling
- Connector restoration in the field
- Data center installation
- Patch cord customization in the field

### Specifications

PARAMETER		VALUE
Insertion Loss	Single-mode (OS1)	Average: 0.25 dB; Max: 0.75 dB
	Single-mode (OS1), Low Loss	Average: 0.10 dB; Max: 0.35 dB
	62.5/125 (OM1)	Average: 0.10 dB; Max: 0.35 dB
	50/125 (OM4)	Average: 0.10 dB; Max: 0.35 dB
Return Loss	Single-mode (OS1)	>65 dB
	62.5/125 (OM1)	>30 dB
	50/125 (OM4)	>30 dB

continued  
→

## FUSEConnect® MPO Splice-On, Field-Installable Connectors with Heat Sleeve

### Ordering Information

AFL NO.*	CONNECTOR TYPE	FIBER TYPE	POLISH	CABLE SIZE		HOUSING COLOR
				ROUND	FLAT	
FUSEMPO-S-SMA-3-F-6	MPO, Female (No Guide Pins)	Single-mode (OS1)	APC	3.0 mm	250 µm	Green
FUSEMPO-S-SMA-3-M-6	MPO, Male (Guide Pins)	Single-mode (OS1)	APC	3.0 mm	250 µm	Green
FUSEMPO-S-LSMA-3-F-6	MPO, Female (No Guide Pins)	Single-mode (OS1), Low Loss	APC	3.0 mm	250 µm	Mustard
FUSEMPO-S-LSMA-3-M-6	MPO, Male (Guide Pins)	Single-mode (OS1), Low Loss	APC	3.0 mm	250 µm	Mustard
FUSEMPO-S-MM6-3-F-6	MPO, Female (No Guide Pins)	Multimode 62.5 µm (OM1)	PC	3.0 mm	250 µm	Beige
FUSEMPO-S-MM6-3-M-6	MPO, Male (Guide Pins)	Multimode 62.5 µm (OM1)	PC	3.0 mm	250 µm	Beige
FUSEMPO-S-OM4-3-F-6	MPO, Female (No Guide Pins)	Multimode , 50 µm (OM4)	PC	3.0 mm	250 µm	Aqua
FUSEMPO-S-OM4-3-M-6	MPO, Male (Guide Pins)	Multimode , 50 µm (OM4)	PC	3.0 mm	250 µm	Aqua

\*Pack of 6 pieces

### Ordering Information – Accessories

DESCRIPTION	AFL NO.
<b>TOOL KIT</b>	
FUSEConnect MPO Tool Kit	FUSEMPO-TL-KT
<b>ACCESSORIES</b>	
FUSEConnect Stripping Tool (3.0 mm, 2.8 mm, 2.0 mm and 1.6 mm)	FUSE-ST-TL
FUSEConnect MPO Heater Attachment Tool	FUSE-HT-TL
MPO Boot Kit for 3.8 mm diameter cable (Pack of 144)	FUSEMPO-BOOT-3.8MM-144
MPO Boot Kit for Jacketed Ribbon (Pack of 6)	FUSEMPO-BOOT-JK-6

### Temperature Specifications

TEMPERATURE RANGE	
Operating Temperature	-40°C to +75°C

### Qualifications

GOVERNING BODY	STANDARD CODE
TIA	604-5-C
IEC	61754-7
GR	1435-CORE Issue 2
FOCIS	FOCIS-5

Contact AFL for further details.