



PARTS LIST			
ITEM	QTY.	PART NUMBER	DESCRIPTION
1	1	DLI4A2-01	INSULATOR, STRAIN, CLEVIS/EYE, 28" LONG, 6" SHEDS, 25KV, INLINE, 36K
2	1	FTDEW30-T	DEAD END, CONTACT WIRE, 300 MCM, CLEVIS W/ 5/8" PIN
3	3	G408-50	THIMBLE, 1/2", OPEN, HDG
4	3	SDE-5107-SS304	DEAD END, GUY GRIP, 1/2" DIA, STAINLESS STEEL, TYPE 304
5	1	SHP213-8099	SHACKLE, ANCHOR, 1/2", PIN 5/8", SML: 24K
6	2	SHP213-8115	SHACKLE, ANCHOR, 5/8", PIN 3/4", SML: 39K
7	*	SSAC-50-19X7	WIRE ROPE, 1/2" DIA, 19X7, TYPE SS 304, BS:20520 LBS
8	1	SV5-204A	STRANDVISE, 1/2" WIRE SIZE, TYPE A BAIL
9	1	TBJE026-512	TURNBUCKLE, JAW/EYE, 3/4" X 9", SML 26k, WITH JAMNUTS

LOCATION		CONTRACT NO		CUST/CONTR	
THIS DRAWING AND ALL INFORMATION ON IT IS THE PROPERTY OF AFL. IT IS CONFIDENTIAL AND IT IS GIVEN TO YOU FOR A LIMITED PURPOSE AND MUST BE RETURNED UPON REQUEST. NEITHER THIS DRAWING OR ANY PART OF IT NOR ANY INFORMATION CONCERNING IT MAY BE COPIED, EXHIBITED, OR FURNISHED TO OTHERS NOR PHOTOGRAPHS TAKEN OF ANY ARTICLE FABRICATED OR ASSEMBLED FROM THE DRAWING WITHOUT THE CONSENT OF AFL.		REVISIONS		DRN BY: AY DRN DATE: 4.30.15 CHK BY: JL CHK DATE: 4.30.15 PA 2015.231.0	
		REV	DESCRIPTION	DATE	BY
				REV 0 FTCW-HSR-01	
				DWG. NO AFLS-FTCW-HSR-01	
				1 OF 1	



FIXED TERMINATION, SINGLE CONTACT WIRE, 25KVAC