

OFI-400 Series Optical Fiber Identifiers



OFI-400

OFI-400C

OFI-400HP

Features

- 5-year product warranty; 3-year recommended calibration interval
- Rugged, hand-held, lightweight, and easy-to-use
- Unique optical head with two-position plunger for use with all fiber types
- Built-in power meter with Set Reference feature

Applications

- Live fiber detection to avoid technician-induced outages
- Fiber identification and tracing with CW or tones
- Core power measurements
- Testing 250 μm , 900 μm , and ribbon fiber or 2 mm and 3 mm jacketed fiber

AFL's OFI-400 Optical Fiber Identifiers are rugged, hand-held, and easy-to-use fiber optic test instruments designed to detect and measure the core power levels of optical signals on single-mode optical fiber without disrupting traffic on that fiber. They are simply clamped onto a fiber and display the presence and direction of traffic, continuous test signals, and modulated test tones. This permits network personnel to easily and quickly identify a specific fiber without the risk of disrupting service. All of AFL's optical light sources are ideal companions to the OFI-400 family of optical fiber identifiers.

No adapters to purchase, store, swap, or misplace: Each OFI-400 uses a unique optical head design featuring a two-position plunger that enables it to be used with 250 μm , 900 μm , and ribbon fiber or 2 mm and 3 mm jacketed fiber. Other brands of optical fiber identifiers require users to purchase, store and change optical plungers each time a different type of fiber is tested.

Low insertion loss for in-service ID tasks: OFI-400's optical heads induces a safe, repeatable macro-bend to the fiber that allows a small amount of light to escape for analysis. The insertion loss induced by the macro-bend is too small to affect the signal on the fiber and the integrity of the fiber is unaffected by the measurement process.

Designed for the real world: The OFI-400 family are simple, easy-to-use tools that feature rugged, drop-proof construction - perfect for inside or outside plant use. Their ergonomically designed macro-bend trigger is comfortable to use and the integrated, backlit LCD display enables them to be used in dimly lit spaces. Each OFI-400 uses readily available 1.5 V AAA batteries which can power thousands of fiber tests before needing to be replaced.

OFI-400 model: The OFI-400 is designed for use with a wide range of single-mode fibers including 250 μm (bare) coated, 900 μm buffered and ribbon fibers or 2 mm and 3 mm jacketed fibers. The OFI-400 is ideal for network personnel involved in installation, reconfiguration, restoration and maintenance tasks that involve bare, buffered, jacketed or ribbon fibers in outside plant pedestals, fiber cabinets, aerial enclosures and inside plant premises demarcation cabinets. The slim design of the OFI-400 head facilitates access in crowded splice trays.

OFI-400C model: Designed specifically for use with 2 mm or 3 mm jacketed single-mode fibers, the OFI-400C is ideal for general purpose maintenance, configuration and installation tasks. The OFI-400C is functionally equivalent to the OFI-400 but includes an optical head design and a calibration scheme optimized for use with jacketed fiber.

OFI-400HP model: The OFI-400HP is designed for use where high levels of optical power are present. This includes fibers carrying a single high-power signal, CWDM or DWDM signals with high total power levels, amplified optical signals, or pump lasers associated with EDFA or Raman amplifiers. When display reaches +23 dBm (200 mW) or greater, the OFI-400HP will display "High" warning indication.

OFI-400 Series Optical Fiber Identifiers

Specifications^a

DETECTABLE SIGNAL RANGE					
FIBER TYPE ^b	PARAMETER	TEST CONDITIONS ^c	OFI-400	OFI-400C	OFI-400HP
250 µm coated fiber (SMF-28 with 250 µm CPC6 coating)	Minimum level detected, average power	1310 nm, CW, Tone, Traffic 1550 nm, CW, Tone, Traffic	-45 dBm -50 dBm	N/A	N/A
	Insertion loss (typical)	@ 1310 nm @ 1550 nm	0.6 dB 2.5 dB	N/A	N/A
3 mm jacketed fiber (SMF-28/28E with 250 µm CPC6 coating and 3 mm, yellow jacket)	Minimum level detected, average power	1310 nm, CW, Tone, Traffic 1550 nm, CW, Traffic 1550 nm, Tone	-30 dBm -33 dBm -33 dBm	-35 dBm -40 dBm -40 dBm	-30 dBm -40 dBm -35 dBm
	Insertion loss (typical)	@ 1310 nm @ 1550 nm	1.0 dB 2.8 dB	1.0 dB 2.8 dB	0.2 to 0.5 dB 0.8 to 1.3 dB

OPTICAL SPECIFICATIONS ^d	OFI-400	OFI-400C	OFI-400HP
Calibrated Fiber and Wavelength	250 µm @ 1550 nm (SMF-28/28E)	3 mm @ 1550 nm (SMF-28/28E)	
Working Fiber Size	250 µm, 900 µm, ribbon, 2 mm and 3 mm jacketed	2 mm and 3 mm jacketed	
Core Power Measurement Range ^e	+13 to -50 dBm @ 1550 nm, 250 µm	+13 to -40 dBm @ 1550nm, 3 mm	+33 to -40 dBm @ 1550 nm, 3 mm
Detector Type	InGaAs		
Wavelength Range	800 - 1700 nm		
Measurement Units	dBm, dB		
Fiber Stress	<100 kPSI max		
Tone Detection	270, 330, 1000, 2000 Hz (±5 %)		

GENERAL SPECIFICATIONS	ALL OFI-400 MODELS
User Interface	Multi 7 segment LCD; 3 LEDs; 1 piezo buzzer
Power	2 x 1.5 V AAA alkaline
Battery Life	>10,000 operations typical
Operation Temperature	-5°C to 50°C 95 % RH (Non-condensing)
Storage Temperature	-30°C to +60°C 95 % RH (Non-condensing)
Dimensions (H x W x D)	21.5 x 3.8 x 2.8 cm (8.5 x 1.5 x 1.1 in)
Weight	168 g (6 oz)

Notes:

- a. All specifications stated above are as measured at 25°C.
- b. 250 µm coated fiber parameters are specified with OFI plunger in the "250 / 900 / RIB" position. 2 mm / 3 mm jacketed fiber parameters are specified with OFI plunger in the "2 mm / 3 mm" position.
- c. CW is a light signal that is not modulated. Traffic is a light signal modulated by high speed user data. Tone is a light signal modulated into a nominal 50 % duty cycle square wave.
- d. Unless noted otherwise, all specifications are typical. Actual results can vary by several dB depending on fiber type, coating material, jacket color, jacket hardness, and other factors.
- e. SMF-28/28E.

OFI-400 Series Optical Fiber Identifiers

Ordering Information

All OFI-400 products include a user's guide, 2 AAA batteries and a soft carry case. Each carries a 5-year warranty and a 3-year recommended calibration interval.

INCLUDES	AFL NO.
Users guide, 2 AAA batteries, soft carry case	OFI-400
Users guide, 2 AAA batteries, soft carry case	OFI-400C
Users guide, 2 AAA batteries, soft carry case	OFI-400HP

Recommended Products



FlexScan® FS300 (quad) and FS200 (single-mode) OTDRs

- SmartAuto® 1-button automated testing for fast results
- LinkMap® color-coded icons for easy troubleshooting
- FleXpress® mode (FS200) completes OTDR test in <5 seconds!
- Integrated Source, Power Meter and VFL



Optical Light Sources

- Encircled Flux Compliant
- 5-Year Product Warranty
- Integrated LED and Laser light sources

Qualifications

CATEGORY	REGULATION/STANDARD	QUALIFICATION
CE Marking	EU	Compliant to relevant EU Directives on health, safety, and environmental protection, and certified with CE marking
Safety /EMC /EMI	IEC	Compliant to IEC 61010-1 for safety requirements for electrical equipment
	EN	Compliant to EN 61010-1 for safety requirements for electrical equipment
	IEC	Compliant to IEC 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 55011 for EMC requirements for industrial, scientific and medical equipment
RoHS	EU	Compliant to EU regulations Directive 2011/65/EU (RoHS 2) and Directive 2015/863 (RoHS 3)

Contact Sales@AFLglobal.com to schedule a demonstration or learn how to buy.

Visit www.AFLglobal.com/Test to learn more about Optical Fiber Identifiers.

International Sales and Service Contact Information available at www.AFLglobal.com/Test/Contacts