

Wall Mount Interconnect Enclosure (WME) with Four LGX® Mounting Positions

AFL's wall mount interconnect enclosure (WME04) provides a convenient convergence point for interconnecting and/or splicing in wall mount applications. Provisioned for up to four LGX compatible adapter plates or optical modules, the enclosure features a well-engineered solution for fiber and cable management on both the ingress and egress openings of the enclosure. Robust steel construction ensures the highest level of protection for sensitive components while integrated roll-formed hinges eliminate possible fiber pinch points while deploying or servicing components within. The WME04 features discrete access doors for provider and customer access which are independently lockable with a common pad-lock or tube-style keyed lock.

Features

- Fits comfortably into new and existing interconnect, cross-connect and co-location environments
- U-shaped cable entry eliminates the need to feed preconnectorized cables through an inconvenient access port
- Modular design fully compatible with Poli-MOD® products and XFM optical cassettes
- Dual doors with separate locking options for flexibility and security
- Available empty, with adapters, or with adapters, splice trays and pigtails pre-installed
- LGX 118 compatible
- Optional splice tray and holder (ordered separately)
- All major connector types are supported

Applications

- Co-Location sites
- Customer premise
- Hub/OTN sites
- Telecommunication closets
- Campus/enterprise environments

Specifications

- Solid steel construction
- Powder coat black textured finish
- Top or bottom cable entry with dust resistant grommets
- Dual-hasp locking/security system
- 24 to 48 fiber patch and splice density
- Four LGX mounting positions
- Physical dimensions: 12.0"H x 16.0"W x 3.63"D



WME-04



WME-04 shown empty



WME-04 shown fully loaded

Wall Mount Interconnect Enclosure (WME) with Four LGX® Mounting Positions

Ordering Information

Empty	
Description	AFL No.
WME04 Empty	WME04E

Half Loaded: WME with Adapter Plates and Adapters Only				
Connector Type	Fiber Count	AFL No.		
		UPC SM (Blue)	APC SM (Green)	PC MM (Beige)
SC	24	WME04AS-USCSM-024000	WME04AS-ASCSM-024000	WME04AS-PSCM6-024000
	48	WME04AH-USFSM-048000	WME04AH-ASFSM-048000	WME04AH-PSFM6-048000
LC	24	WME04AS-UDLSM-024000	WME04AS-ADLSM-024000	WME04AS-PDLM6-024000
	48	WME04AH-UDLSM-048000	WME04AH-ADLSM-048000	WME04AH-PDLM6-048000
ST	24	WME04AS-USTSM-024000	—	WME04AS-PSTM6-024000
	48	WME04AH-USTSM-048000	—	WME04AH-PSTM6-048000

loaded: WME with Adapter Plates/Adapters/Splice Trays/Pigtail (900 µm Tight Buffered Fibers 3 meters in Length)					
Connector Type	Fiber Count	AFL No.			
		UPC SM (Blue)	APC SM (Green)	PC MM 62.5 µm (Beige)	PC MM 50 µm (Black)
SC	24	WME04FS-USCSM-024120	WME04FS-ASCSM-024120	WME04FS-PSCM6-024120	WME04FS-PSCM5-024120
	48	WME04FH-USFSM-048140	WME04FH-ASFSM-048140	WME04FH-PSFM6-048140	WME04FH-PSFM5-048140
LC	24	WME04FS-UDLSM-024120	WME04FS-ADLSM-024120	WME04FS-PDLM6-024120	WME04FS-PDLM5-024120
	48	WME04FH-UDLSM-048140	WME04FH-ADLSM-048140	WME04FH-PDLM6-048140	WME04FH-PDLM5-048140
ST	24	WME04FS-USTSM-024120	—	WME04FS-PSTM6-024120	WME04FS-PSTM5-024120
	48	WME04FH-USTSM-048140	—	WME04FH-PSTM6-048140	WME04FH-PSTM5-048140

Accessories	
Description	AFL No.
Splice Tray Kit: Single Fusion 12F, 2RU, WME02, WME04, 3 Splice Trays	FM002827-3
Splice Tray Kit: Single Fusion 12F, 2RU, WME02, WME04, 4 Splice Trays	FM002827-4

Connector/Adapter Key

Type	Description
ASC	Angle Polish SC (ZR) sleeve-SM
ASF	Angle Polish SC Duplex (ZR) sleeve-SM
PSC	Physical Polish SC (PB) sleeve-MM
PSF	Physical Polish SC Duplex (PB) sleeve-MM
USC	Ultra Polish SC with (ZR) sleeve-SM
USF	Ultra Polish SC Duplex (ZR) sleeve-SM
PST	Physical Polish ST (PB) sleeve-MM
UST	Ultra Polish ST (ZR) sleeve-SM
ADL	Angle Polish LC Duplex (ZR) sleeve-SM
PDL	Physical Polish LC Duplex (PB) sleeve-MM
PLC	Physical Polish LC (PB) sleeve-MM
UDL	Ultra Polish LC Duplex (ZR) sleeve-SM
ULC	Ultra Polish LC (ZR) sleeve-SM