





Multi-Drop Thimble Eye (ordered separately)



Drop Dead End shown with Single-Drop Thimble Eye



Drop Dead End works with both Round and Flat Drop Cable


## **Drop Dead End for ADSS Cable – Medium**

The Drop Dead Ends are designed for use on ADSS cable in Medium NESC Loading environments.

Available with AFL's Multi-Drop Thimble Eye (second photo) which is used to anchor aerial round drop cables to the distribution structure. The Thimble Eye has uniform radial slots that can accommodate up to four formed wire dead ends per thimble eye and support tensioning up to 90 degrees from the installation hardware.

## **Features**

- Designed for use in Medium NESC Loading environments (see map below)
- Works with both round and flat drop cable
- Made of Aluminum Alloy material
- Installation tension is ≤maximum of rated cable load
- Easy and quick installation
- No special tools or hardware required for installation
- Small, requiring less storage space
- Five-rod construction
- Available with Multi-Drop Thimble Eye (ordered separately)



## **Ordering Information**

To order with Drop Dead End with Thimble Eye, add suffix "TE" to AFL No.

AFL NO.	CABLE OD (in.)	LENGTH (in.)	TENSILE STRENGTH (lbs)	WEIGHT (lbs)	COLOR CODE
ADELD4F309/341	0.309 - 0.341	41.3	<mrcl< td=""><td>0.33</td><td>Blue</td></mrcl<>	0.33	Blue

For more information on the optional Multi-Drop Thimble Eye (ordered separately), see specification sheet.