

# Apex® Fiber Optic Splice Closures

Broadband deployment doesn't have to be complicated. Simplify the process with AFL's suite of Apex Splice Closures. With a compact, high-density design, and full BEAD compliance, the Apex closure line is built for speed, space efficiency and long-term reliability. Discover how Apex helps service providers deploy broadband with ease - helping them stay compliant, confident and ahead of the curve.

**AFL**

[www.AFLglobal.com](http://www.AFLglobal.com)

864.433.0333



APEX MODEL	X-1	X-2S	X-2	X-3	X-3H
Dimensions (L x D, in/cm)	19 x 9 (48 x 23)	20 x 12 (51 x 30)	25 x 12 (64 x 30)	32 x 14 (81.3 x 35.6)	32 x 14 (81.3 x 35.6)
Weight (lbs/kg)	10 (4.5)	22 (10)	25 (11.3)	30 (13.6)	30 (13.6)
Splice Capacity (Single/Mass (Standard)/ Mass (SpiderWeb Ribbon® (SWR®)))	144 / 432 / 864	288 / 864 / 1,728	576 / 1,728 / 3,456	864 / 2,592 / 5,184	2,592 Ribbon / 6,912 SWR
Splice Tray Capacity	3	6	6	6	8
Cable Ports (Max Drop Cables)	4 (up to 8)	6 (up to 16)	6 (up to 16)	6 (up to 16)	6
Cable Diameter (in/mm)	0.40-1.10 (10-28)	0.40-1.10 (10-28)	0.40-1.10 (10-28)	0.40-1.46 (10.16-37)	0.40-1.46 (10.16-37)
Waterhead Test	20 ft	20 ft	20 ft	15 ft	15 ft