


Connector Kits for Opti-Guard and SB01 Splice Enclosures— Black Jacket Cable

Connector Kit: All-Dielectric Self-Supporting Fiber Optic Cable



All-Dielectric Self-Supporting Connector Kit

BCK

Black Jacket Cable
Connector Kit

XXX/XXX


Range Code in
Decimal Inches
(see Table 1 below)

F

Blank = No Additional Connector
Assembly Required
F = 1" Flex Conduit Connector Required

Ordering Example: For 0.528" diameter ADSS, the AFL number is BCK522/537.

Connector Kit: Loose Tube Fiber Optic Cable



Armored Loose Tube Connector Kit

BCK

Black Jacket Cable
Connector Kit

XXX/XXX

Range Code in
Decimal Inches
(see Table 1 below)

B

Options
Blank = No Additional Connector
Assembly Required
F = 1" Flexible Conduit Connector Required
A = Armor Ground Assembly Required
B = Armor Ground Assembly and 1" Flexible
Conduit Connector Required

Ordering Example: For 0.510" armored loose tube (duct) cable with flexible conduit and armor ground connections, the AFL number is BCK507/521B.

Table 1

RANGE CODE	CABLE DIAMETER RANGE	
	MIN.	MAX.
225/240	0.225	0.240
241/255	0.241	0.255
256/271	0.256	0.271
272/286	0.272	0.286
287/302	0.287	0.302
303/318	0.303	0.318
319/333	0.319	0.333
334/349	0.334	0.349
350/365	0.350	0.365
366/380	0.366	0.380
381/396	0.381	0.396
397/412	0.397	0.412
413/427	0.413	0.427
428/443	0.428	0.443
444/459	0.444	0.459
460/474	0.460	0.474
475/490	0.475	0.490

RANGE CODE	CABLE DIAMETER RANGE	
	MIN.	MAX.
491/506	0.491	0.506
507/521	0.507	0.521
522/537	0.522	0.537
538/553	0.538	0.553
554/568	0.554	0.568
569/583	0.569	0.583
584/599	0.584	0.599
600/615	0.600	0.615
616/630	0.616	0.630
631/646	0.631	0.646
647/662	0.647	0.662
663/677	0.663	0.677
678/693	0.678	0.693
694/708	0.694	0.708
709/727	0.709	0.727
728/740	0.728	0.740

continued →