

Installing AFL LL-400sx in Channell Pedestal (Channell Part no. OP12126C1B1LH1A08)

General

AFL's LL-400sx can be mounted into the Channell Optimus Pedestal (part number OP12126C1B1LH1A08, 12126 Dual Offset Brackets, light green Dual Cut pedestal) by moving the top mounting bracket prior to installation. This will allow mounting the LL-400sx using the pre-installed 10/32 inserts on the back of the enclosure using the (2) bolts included in the LL-400sx.



LL-400sx in OP1212



OP1212 Pedestal

Modifications Needed to Pedestal

The upper mounting bracket will need to be moved from its original shipping position. This can be done with a standard Can Wrench (216 tool).

Installing AFL LL-400sx in Channell Pedestal (Channell Part No. OP12126C1B1LH1A08)

Installation Steps

1. For ease of access, remove the metal curved rod by loosening the two nuts holding them in place (**Figure 1**).
2. Remove the top bracket and reposition it in the first mounting position from the top crossbar. Ensure the nuts are not threaded too far that the bracket is bent (**Figures 2 and 3**).
3. Using the supplied mounting bolts (10/32 x 0.5) and washers, attach the top bolt in the upper-center slot of the top bracket. Install bolt but do not fully tighten (**Figure 4**).
4. Align the lower insert with the upper-center slot of the bottom bracket and insert bolt. Ensure enclosure is straight and door will clear pedestal base. Tighten the mount bolts on the back of the LL-400sx (**Figure 4**).
5. Slide the metal curved rod back into its place and tighten the nuts to hold them in place.



Figure 1



Figure 2



Figure 3



Figure 4