
THIS DRAWING AND ALL INFORMATION ON IT IS THE PROPERTY OF AFL. IT IS CONFIDENTIAL AND IT IS GIVEN TO YOU FOR A LIMITED PURPOSE AND MUST BE RETURNED UPON REQUEST. NEITHER THIS DRAWING OR ANY PART OF IT NOR ANY INFORMATION CONCERNING IT MAY BE COPIED, EXHIBITED, OR FURNISHED TO OTHERS NOR PHOTOGRAPHS TAKEN OF ANY ARTICLE FABRICATED OR ASSEMBLED FROM THE DRAWING WITHOUT THE CONSENT OF AFL.

ITEM NO

DWG NO
D-6997A



MATERIAL
ALUMINUM BRONZE ASTM B30
U-BOLTS, NUTS, & LOCKWASHERS - GALVANIZED HIGH STRENGTH STEEL
CLEVIS PIN-GALVANIZED STEEL
COTTER KEY-STAINLESS STEEL

18.17 LBS

CABLE RANGE
500MCM (.814 DIA) -1000MCM(1.152 DIA.)

NOTES:
1. MIN ULTIMATE STRENGTH LOAD; 40,000 LBS
2. WORKING LOAD: 16,200 LBS
3. U-BOLTS TO BE TORQUED TO 70 FT-LBS

LOCATION	CONTRACT NO	CUST / CONTR

REVISIONS

REV	DESCRIPTION	DATE	BY	APR
2	RE-DRAWN IN INVENTOR	2-12-10	LK	EP

DRN BY: CV
DRN DATE: 2-6-91
CHK BY: PG
CHK DATE: 2-6-91

AFL DOSSERT®

CLAMP, STRAIN ANGLE 500 MCM - 1000 MCM

REV 2 | SECL-100-H-4-RR | 1 OF 1