THIS DRAWING AND ALL INFORMATION ON IT IS THE PROPERTY OF AFL. IT IS CONFIDENTIAL AND IT IS GIVEN TO YOU FOR A LIMITED PURPOSE AND MUST BE RETURNED UPON REQUEST. NEITHER THIS DRAWING OR ANY PART OF IT NOR ANY INFORMATION CONCERNING IT MAY BE COPIED, EXHIBITED, OR FURNISHED TO OTHERS NOR PHOTOGRAPHS TAKEN OF ANY ARTICLE FABRICATED OR ASSEMBLED FROM THE DRAWING WITHOUT THE CONSENT OF AFL.

ITEM NO:

DWG. NO:





MATERIAL:
INSULATOR END - DUCTILE IRON, H.D.G*
INSULATOR ROD - 3 1/2" EPOXY, FIBERGLASS
SKIRTS - EPDM RUBBER
U-BOLTS, BOLTS, NUTS & LOCKWASHERS - STAINLESS STEEL

BOLT SIZES	WRENCH/ SOCKET SIZES	TORQUE VALUES (FT-LBS)
1/2-13	3/4 HEX	45

WT: 27.78 LB

* = HOT DIP GALVANIZED

LOCATION	CONTRACT NO	CUST / CONTR

REVISIONS

REV	DESCRIPTION	DATE	BY	APR

DRN BY: BR
DRN DATE: 07.18.17
CHK BY: GC
CHK DATE: 07.19.17
PA 2015.231.0

AFL DOSSERT®

INSULATOR, STRUT, PIPE TO PIPE, 2" IPS, 30 5/8" OAL, 25KV

REV 0 | PART NO: SA-B0406-02 | 1 OF 1