



ITEM #	QTY.	PART NUMBER	DESCRIPTION
7	*	SSAC-37	WIRE ROPE, 3/8", L ON ORDER
15	1	CSNP-38PL	SLEEVE, COMPRESSION 3/8", PLAIN
18	1	G408-38	THIMBLE, 3/8", OPEN, HDG
84	2	ESC200	CAP, 2" IPS SEAL, EXTERNAL PLASTIC
204	2	PBA-HCB-A01	POLE BAND W/ HINGE
376	1	ESC75	END CAP, 3/4" IPS
385	1	CSA75-7200-A02-AA	STRAIGHT STEADY ARM, 3/4" IPS
599	*	PGSB200-40-L	PIPE, 2" IPS X SCH 40 WALL, ASTM A106, GR B, TYPE E
640	1	DELA90-FR-AA	LINK RING-TONGUE 90 DEG, ALUM
690	1	CSCA100-6-5AA	CLAMP, INSULATED CONTACT SWIVEL, CW:350 MCM
778	1	ADB200-S-AA	ADJUSTABLE DROP BRACKET, 2" IPS
1101	1	MSCAI821-20050S-A06	INSULATOR, MESSENGER SADDLE 2" IPS, MW:500 SINGLE
1352	2	INS-ST2-A13	STRUT INSULATOR, 2" IPS, 750 VDC
1359	2	TPSC200-C-63	PIPE TO EYE END CLAMP, 2" IPS ALUM
1366	3	BSCA200-63-A03	CLEVIS PIPE CLAMP, 2" IPS, 5/8" PIN. ADDED CLEARANCE

LOCATION

CONTRACT NO

CUST/CONTR

THIS DRAWING AND ALL INFORMATION ON IT IS THE PROPERTY OF AFL. IT IS CONFIDENTIAL AND IT IS GIVEN TO YOU FOR A LIMITED PURPOSE AND MUST BE RETURNED UPON REQUEST. NEITHER THIS DRAWING OR ANY PART OF IT NOR ANY INFORMATION CONCERNING IT MAY BE COPIED, EXHIBITED, OR FURNISHED TO OTHERS NOR PHOTOGRAPHS TAKEN OF ANY ARTICLE FABRICATED OR ASSEMBLED FROM THE DRAWING WITHOUT THE CONSENT OF AFL.

REV	DESCRIPTION	DATE	BY	APR
1	REDRAWN FOR CORRECT CONFIGURATION	08.11.14	EE	JL

DRN BY: DK
DRN DATE: 1.28.14
CHK BY: JL
CHK DATE: 1.28.14
PA2013.0

AFL

DOSSERT

CANTILEVER PUSH OFF, MED LOAD,
MW:500, CW:350

REV/P/N: 1
AFLS-CA0-LR-07

DWG. NO: AFLS-CA0-LR-07

1 OF 1