

| LOCATION | CONTRACT N |
|---|-------------|
| | |
| | REVISIONS |
| DRAWING AND ALL INFORMATION ON IT IS THE PROPERTY OF AFL. | DESCRIPTION |
| IUST BE RETURNED UPON REQUEST. NEITHER THIS DRAWING OR | |
| ART OF IT NOR ANY INFORMATION CONCERNING IT MAY BE | |
| D, EXHIBITED, OR FURNISHED TO OTHERS NOR PHOTOGRAPHS | |
| ING WITHOUT THE CONSENT OF AFL. | |
| | |

| | 2 | |
|---------|---|--|
| · · · | PARTS LIST | |
| BER | DESCRIPTION | |
| 01 | CLAMP, PIPE, CLEVIS, 2" IPS, 3/4" PIN, EXT, AL | |
| | COTTER PIN, HUMPBACK 1/4" X 2-1/2", SS | |
| B-15-02 | STEADY ARM, 1-1/2" IPS, 3.78 FT, 1 BEND, SCH 80, AL | |
| | SLEEVE, COMPRESSION, 3/16", PLAIN | |
| | LINK, EYE TO EYE, INLINE, 13/16" HOLES, 6" CENTERS, HDG | |
| 18-01 | PIPE CLAMP, DROP, 2" IPS TO 2" IPS, BRZ | |
| | CAP, 2" IPS SEAL, EXTERNAL PLASTIC, BLACK | |
| | THIMBLE, 3/16", OPEN, HDG | |
| | PLUG, 2" IPS, INTERNAL PLASTIC, SCH 80 PIPE SEAL | |
| | CLAMP, CONTACT WIRE, BRIDLE SUPPORT | |
| U | CLAMP, PIPE, 2" IPS, 3/16" BRIDLE, SWIVEL, NON-INSULATED, BRZ | |
| | PIPE, 2" IPS, SCH 80, ASTM A53, GR B, HDG/ASTM A123 | |
| | PIPE CLAMP, 2" IPS, DOUBLE STEADY ARM, FR, AL | |
| | INSULATOR, STRUT, TONGUE, 2" IPS, 25kV | |
| | WIRE ROPE, 3/16" DIA, 19X7, TYPE SS 304, BS:3300 LBS | |
| | BRACKET, STATIC WIRE CLAMP MTG | |
| | CLAMP, STATIC WIRE, AL, FITS 1/0 (0.373D) | |
| 3 | CLAMP, SWIVEL CONTACT WIRE, 4/0 - 350 MCM, 3/8"-16 MALE THD | |
| 5-01 | CLAMP, PIPE EYE, 2" SCH 80, HDG, INTERNAL | |
| | | |